



technology | environment | partnership

TD/SD 302



Specification TD/SD 302

Pressure:	30-300bar / 423-4233psi*
Flow:	18l / min 1080l / h*
Pump:	Hawk industrial pump
Max Temp:	99°C-150°C**
Engine model:	Kubota D722
Engine power:	14kw / 19hp
Fuel/cylinders:	Diesel / 3 cylinder
Fuel tank:	77litres
Water tank:	345litres
Trailer dimensions:	277x160x160cm
Van mount dimensions:	134x115x127cm
Weight TD/SD:	620/460kg

* infinitely variable pressure and volume

** higher temperature can be achieved at reduced flow

Standard Features/Equipment

Water cooled diesel engine

Spray gun and lance

30 meters water supply hose on reel

30 meters high pressure hose on reel

Safety Features

Automatic engine cut out on:

- Open engine lid compartment
- Low water
- Closed chimney lid

Flame surveillance (for automatic safety cut out)

Current temperature display

Oil pressure sensor

Engine overheat protection

Diesel Trailer or van mounted

Ideal Applications



Optional Equipment

BKX unloader	Descale system
Hazard lights	Anti freeze system
Automatic throttle control	Remote control
Electric hose reels	Chemical injection system

Accessories

Turbo lance and nozzles
Floor tool
Wet sand blasting kit
Abrasive cleaning kit
Extension hose and reels
Drain cleaning and other nozzles
Spray guns and lances
Tank cleaning head



This model is also available with upgraded braked chassis, 1300kg trailer or a boogie trailer

Mandal Alle 3, DK 5500 Middelfart, Denmark

T: 0045 64 41 5555 • F: 0045 64 41 7555 • E: info@aquila.dk

aquilapressurewashers.com